

ESTORIL COLLECTION

Bovine leather grain

Slightly corrected and embossed

Through dyed, one colour

Firm feel

Tough and durable

	Regulatory Standard		Unit of Measurement
Average hide size		4.3 - 5.0	sq mtr
Thickness	ISO 2589	1.0 - 1.2	mm
Colour Fastness to Rubbing (Dry)	UNI EN ISO 11640; ISO 105-A02	1500 / ≥ 4	Grey Scale
Colour Fastness to Rubbing (Wet)	UNI EN ISO 11640; ISO 105-A02	500 / ≥ 4	Grey Scale
Colour Fastness to Rubbing (Alkali Sweat Solution)	UNI EN ISO 11640; ISO 105-A02; ISO 105 E04	80 / ≥ 4	Grey Scale
Strength of finish adhesion	ISO 11644	≥ 4	N/cm
Tensile Strength	ISO 3376	≥ 130	N
Tear Resistance	ISO 3377-1	≥ 25	N
Stitch Tear Resistance	ISO 23910	≥ 60	N
Behaviour at permanent folding - 50,000 Cycles	UNI - ISO 5402	No Damage	Visual Evaluation
Colour Fastness to light - 72 h	ISO 105 B06	≥ 4	Grey Scale
Aging	4h @ 70 Degrees Celsius	min 4	Visual Evaluation
Flammability	FMVSS 302	< 100	mm/min
ph Value	ISO 4045	≥ 3, 5	
Difference figure where ph <4 or >10	ISO 4045	≤ 0.7	